

Technical data:

Explosion Protection	: Ex de IIB T6
Conforming to	: Standards IEC 60079-1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP66 acc. To IEC 60529
Ambient Temp. (Ta)	: - 5 °C to+ 50 °C
Rated Voltage	: 220 - 240 V AC 50/60Hz. Output 12V DC
Lamp	: 1 x 10w. For Flu. , 2 x 9w. For Compact Flu.
LED Life	: 35000 Hrs.
LED Watt. (NEW PRODUCT)	: 20 x 0.5w. (10w.)
Protection class for UL.	: Class I, Division 1or 2 Group. C,D



Specification:

Body material	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032(GREY)
Lens	: Heat and impact resistant clear glass
Sing face	: White, Green acrylic with red, white color letters.



Catalogue Numbers:

Lamp Watts	Temp. Class (Surface Temp.)		Cat., No.
	40 C Ta	55 C Ta	
Fluorescent			
1 x 10 W.	T6	T6	EXIT110F
Compact Fluorescent			
2 x 9 W.	T6	T6	EXIT209F
LED LAMP			
20 x .5w. (10w.)	T6	T6	EXIT2010L

Dimension :

